

# TecnoGen POWER GENERATORS IV74TSX

## Enermax Generator



### Features & Benefits

- Iveco/FPT engine coupled to a Leroy Somer alternator providing 61.5 kW of standby and 56 kW of prime power.
- Sealed doors and 2" thick insulation throughout enable TecnoGen to have a 65 dBA rating at load
- Easy to use deep-sea electronic controller to help keep track of all vital stats
- Heavy-duty tandem axle trailer enables easy balanced towing.
- External fuel hook-ups are standard allowing for quick connection to additional fuel cells



Toll Free (855) 303-7900  
Fax (856) 351-9352  
sales@ftgequipment.com  
www.ftgequipment.com

FTG Equipment Solutions, Inc., 399 North Virginia Avenue, Carney's Point, NJ 08069

Specifications are subject to change without notice. FTG is not responsible for typographical errors.

## Specifications

MODEL	IV74TSX
SERIES	ENERMAX
<b>GENERATOR SPECS</b>	
STANDBY (kW)	61.5 kW (76.8 kVA)
PRIME (kW)	56 kW (70 kVA)
RPM	1800
FREQUENCY (Hz)	60
SOUND LEVEL @ 23 FEET	65 dB(A)
CONTROLLER BRAND	Deep Sea
CONTROLLER MODEL	DSE7310
ALTERNATOR MAKE	Leroy Somer
ALTERNATOR MODEL	LSA 44.352
SYSTEM VOLTAGE	12V
<b>VOLTAGE SELECTION</b>	
<b>AMPS</b>	
Single Phase 120V	192A
Single Phase 240V	192A
Three Phase 240V	182A
Three Phase 480V	92A
<b>ENGINE SPECS</b>	
MAKE	Iveco/FPT
MODEL	NEF45SM2X
EPA LEVEL	Tier 3 Flex
No. Cylinders	4
HP	90
FUEL CAPACITY (Gallons)	49
EXTERNAL FUEL VALVE	YES
FUEL CONTAINMENT	110%
<b>FUEL CONSUMPTION</b>	
80%	3.4 g/h
RUN TIME @ 80% LOAD	14.5 hrs
<b>WEIGHTS AND DIMENSIONS</b>	
<b>SKID W/O TRAILER</b>	
WEIGHT (lbs.)	3615lbs.
LENGTH (in.)	100
WIDTH (in.)	45
HEIGHT (in.)	73



Toll Free (855) 303-7900  
 Fax (856) 351-9352  
[sales@ftgequipment.com](mailto:sales@ftgequipment.com)  
[www.ftgequipment.com](http://www.ftgequipment.com)

FTG Equipment Solutions, Inc., 399 North Virginia Avenue, Carney's Point, NJ 08069